



Combi hot tapping set Gas

For hot tapping steel, cast iron, concrete, PE and PVC pipelines under pressure using safety valves.

The combi-hot tapping set can be used for drilling pipeline under pressure up to 500 mbar without leakage of gas. The safety valve ensures no leakage of gas during hot tap activities.

Composition

Hot tapping tool LB493B

Drilling rod Ø20mm square 16 mm, 3/8" male, L=510 mm

Drilling rod Ø20mm square 16 mm, 3/8" male, L=600 mm

Ratchet square 16 mm female

Adaptor BG 1 ½"

Adaptor BG 2"

Adaptor BG 2 ½"

Adaptor AB 1 ½"

Adaptor 1"x 1 ¼ " male/female

Hot tapping tool P900

Drilling rod Ø16 mm, 3/8" male, L= 400 mm

Drilling rod Ø16mm 3/8" male, L= 300 mm

Twist iron

Hex wrench 2 mm

Centre drill type MPD4

Cuttersleutel for 1004 cutter

Cutter grease

Set of o-rings LB-493B

Set o-rings for P900

Transport case 55cm + int 1600

Cutter 1004 St. Ø49.0mm

Cutter 1004 St. Ø39.0mm

Cutter 1004 St. Ø29.5mm

Cutter 1004 St. Ø22.4mm

Cutter 1006 AC Ø49.0mm

Cutter 1006 AC Ø39.0mm

Cutter 1006 AC Ø29.5mm

Cutter 1006 AC Ø22.4mm

Cutter 1003 PE Ø49.0mm

Cutter 1003 PE Ø39.0mm

Cutter 1003 PE Ø29,5mm

Cutter 1003 PE Ø22,4mm

Peel drill PVC Ø49,0 mm

Peel drill PVC Ø39,0 mm

Peel drill PVC Ø29,5 mm

Peel drill PVC Ø22,4 mm