



Steel Body Pig type KL-BD-G5

For the bidirectional calibration of pipelines.

Dimensions and weight

| Size | Total length (mm) | Distance between front and rear cup (mm) | Weight (kg) |
|------|-------------------|--|-------------|
| 6" | 295 | 165 | 3.1 |
| 8" | 349 | 215 | 4.3 |
| 10" | 430 | 270 | 7.7 |
| 12" | 485 | 320 | 9.3 |
| 14" | 547 | 355 | 15.8 |
| 16" | 600 | 400 | 20.6 |
| 18" | 608 | 460 | 60.0 |
| 20" | 658 | 510 | 90.0 |
| 22" | 716 | 560 | 114.0 |
| 24" | 766 | 610 | 127.0 |
| 26" | 824 | 660 | 151.0 |
| 28" | 874 | 710 | 171.0 |
| 30" | 942 | 770 | 209.0 |
| 32" | 992 | 820 | 225.0 |
| 34" | 1050 | 870 | 280.0 |
| 36" | 1100 | 920 | 313.0 |
| 38" | 1154 | 970 | 352.0 |
| 40" | 1204 | 1020 | 393.0 |
| 42" | 1262 | 1070 | 430.0 |
| 44" | 1312 | 1120 | 482.0 |
| 46" | 1370 | 1170 | 527.0 |
| 48" | 1420 | 1220 | 561.0 |
| 56" | 1640 | 1420 | 761.0 |

Specifications subject to change without notice.